




# RackGuard Guardrail



## SPECIFICATIONS

<b>Angle of impact</b>	45°	90°	180°
Tested impact energy (Joules)	800	1000	800
Equivalent vehicle weight (kg)	2000	2000	2000
Equivalent vehicle speed (km/h)	3.2	3.6	3.2
<b>Material Properties</b>			
Temperature <b>MEMAPLEX</b>	±	-15°C to +50°C	
Temperature <b>MEMAPLEX</b>	±	-40°C to +30°C	
Chemical Resistance		Excellent - ISO / TR 10358	
Fire Rating		HB	
Food Contact		Yes	
Toxicity		None	
Conductivity		No	
<b>Environment</b>			
CO <sub>2</sub> / RackGuard		2.142	
Recyclability		100%	

## DIMENSIONS



\* iFlex RackGuards are also available in 400mm, 1000mm and bespoke sizes, as well as with internal rubber lugs. All iFlex RackGuards are available in the Memaplex FR option.

Terms and conditions apply

## COMPONENTS



Part Code	Description	A - Rack width (max)	B - Rack depth (max)
P-03-01-0017	RackGuard (S) SL - 600mm	102	45
P-03-01-0021	RackGuard (S) ML - 600mm	102	68
P-03-01-0025	RackGuard (S) LL - 600mm	102	80
P-03-01-0018	RackGuard (S) SLR - 600mm	85	45
P-03-01-0022	RackGuard (S) MLR - 600mm	85	68
P-03-01-0026	RackGuard (S) LLR - 600mm	85	80
P-03-01-0029	RackGuard (L) SL - 600mm	126	75
P-03-01-0030	RackGuard (L) SLR - 600mm	112	75
S-01-02-0011	RackGuard Tool Set		



Authorised reseller address

Christian Berner Oy +358 9 2766 830  
infofi@christianberner.com  
christianberner.fi

**CHRISTIAN  
BERNER**