

# BETTER IN ROTARY VALVES

Rotary Airlocks and Blowing Seals



 **tbma**

[www.tbma.com](http://www.tbma.com)

SAMPLING • DOSING • MIXING • STORAGE • CONVEYING • DEDUSTING • DISCHARGING • FILLING • ENGINEERING

## HIGH DUTY



**Type H-AR**

**Application:**

- Mounted below powder hoppers or as dust explosion barrier
- Dosing, pneumatic conveying

**Features:**

- ATEX 95 certified
- Flange size: DN 150 - DN 500
- Volume: 2,5 - 125 ltr/rev
- Body and end covers: cast iron or stainless steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar
- Certified dust-explosion and flameproof up to 10 bar



**Type H-GR**

**Application:**

- Pneumatic conveying

**Features:**

- ATEX 95 certified
- Flange size: DN 150 - DN 350
- Volume: 2,5 - 58 ltr/rev
- Body and end covers: cast iron or stainless steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar



**Type H-AX**

**Application:**

- Mounted below powder hoppers for abrasive and/or mildly cohesive products
- Dosing, pneumatic conveying.

**Features:**

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (square/circular)
- Volume: 2,5 - 34 ltr/rev
- Body and end covers: cast iron
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar

## MEDIUM DUTY



**Type R-AX**

**Application:**

- Mounted below powder hoppers for abrasive and/or mildly sticky products
- Dosing, pneumatic conveying of non-abrasive products

**Features:**

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (square/circular)
- Volume: 2,5 - 34 ltr/rev
- Body and end covers: cast iron
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Max. operating pressure differential 1 bar



**Type M-AX**

**Application:**

- Mounted below powder hoppers for abrasive and/or mildly sticky products
- Dosing, pneumatic conveying of non-abrasive products

**Features:**

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (circular)
- Volume: 2,5 - 58 ltr/rev
- Body and end covers: cast iron
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Max. operating pressure differential 1 bar

## LIGHT DUTY



**Type S-AX**

**Application:**

- Below dust filters and cyclones

**Features:**

- ATEX 95 certified
- Flange size: DN 250 (square/circular)
- Volume: 9,5 ltr/rev
- Body and end cover: cast iron
- Corrosion/abrasion resistant coatings optional
- Rotor: steel
- 8 blade rotor with PUR rotor blades
- Max. operating pressure differential 0,5 bar

# ATEX 95

### Special executions

- Quick-release rotor in various executions
- High temperature resistant execution up to 600°C
- Larger executions available up to 547 ltr/rev
- Horizontal metering rotary valve execution
- Sanitary valve execution
- Mobile valve execution
- Pulsed air injection system



**tbma europe bv**

P.O. Box 140 NI-2210 AC Noordwijkerhout - Holland  
Delfweg 18 NI-2211 VM Noordwijkerhout - Holland  
Phone: +31(0)252 37 50 68 Fax +31(0)252 37 54 36  
E-mail: info@tbma.com www.tbma.com

For more information: